Printing date 20.05.2021 Version number 48 Revision: 20.05.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name DEICHMANN Universalspray 300 ml GB

· Article number: 18233089000

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture impregnation spray for leather
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Salzenbrodt GmbH & Co KG

Internationale Schuh- und Lederpflege

Hermsdorfer Straße 70

D-13437 Berlin

Tel.: +49 30 41404-512

· Informing department:

Product Safety Departement, direct call +49 30 41404545; Mobil +49 162 1096464 e-mail: productsafety@collonil.de

· 1.4 Emergency telephone number:

In case of medical emergency: Poison advisory center Berlin Tel.+49(0)30/30686700

Transport of dangerous goods:

Fire Brigade Bayer AG Tel.+49(0)30/4681-4208

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Aerosol 1

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2 H315 Causes skin irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- · Hazard pictograms GHS02, GHS07, GHS09
- · Signal word Danger
- · Hazard-determining components of labelling:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

(Contd. on page 2)

Printing date 20.05.2021 Version number 48 Revision: 20.05.2021

Trade name DEICHMANN Universalspray 300 ml GB

P102 Keep out of reach of children.

(Contd. of page 1)

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- *P261* Avoid breathing vapours/spray.
- P271 Use only outdoors or in a well-ventilated area.
- P312 Call a POISON CENTER/doctor if you feel unwell.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- P501 Dispose of contents/container in accordance with local regulations.
- · 2.3 Other hazards

The product evidently does not contain any organically bonded halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: waterproofing agents in hydrocarbon solvents, filled with propellant

· Dangerous components:		
CAS: 64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	50-100%
EC number: 921-024-6	♦ Flam. Liq. 2, H225; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ Skin Irrit. 2, H315; STOT SE 3, H336	
CAS: 106-97-8	butane	10-<25%
EINECS: 203-448-7	📀 Flam. Liq. 1, H224	
CAS: 74-98-6	propane	2.5-<10%
EINECS: 200-827-9	📀 Flam. Liq. 1, H224	
CAS: 141-78-6	ethyl acetate	< 2.5%
EINECS: 205-500-4	🚸 Flam. Liq. 2, H225; 🗘 Eye Irrit. 2, H319; STOT SE 3, H336	

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation In case of unconsciousness bring patient into stable side position for transport.
- · After skin contact Instantly wash with water and soap and rinse thoroughly.
- · After eye contact Rinse opened eye for several minutes under running water.
- · After swallowing In case of persistent symptoms consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed

Daze

Breathing difficulty

Dizziness

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents

Water.

Water with a full water jet.

(Contd. on page 3)

Printing date 20.05.2021 Version number 48 Revision: 20.05.2021

Trade name DEICHMANN Universalspray 300 ml GB

(Contd. of page 2)

- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away. see item 7.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Inform respective authorities in case product reaches water or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep containers tightly sealed.

Store in cool, dry place in tightly closed containers.

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Open and handle container with care.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Buildup of explosive mixtures possible without sufficient ventilation. Keep out of reach of children.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and containers:

Store in cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed containers.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 4)

Printing date 20.05.2021 Version number 48 Revision: 20.05.2021

Trade name DEICHMANN Universalspray 300 ml GB

(Contd. of page 3)

· Components with critical values that require monitoring at the workplace:

CAS: 106-97-8 butane (10-25%)

WEL Short-term value: 1810 mg/m³, 750 ppm

Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

CAS: 141-78-6 ethyl acetate (<2.5%)

WEL Short-term value: 1468 mg/m³, 400 ppm Long-term value: 734 mg/m³, 200 ppm

- · Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls Not applicable
- · Personal protective equipment
- · General protective and hygienic measures

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

Only during spraying without adequate removal by suction.

· Protection of hands:

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Nitrile rubber, NBR

Fluorocarbon rubber (Viton)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Fluorocarbon rubber (Viton)

· Eye protection: Tightly sealed safety glasses.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Aerosol
Colour: Colourless

Smell: Characteristic
Odour threshold: Not determined.

· pH-value: Not determined.

(Contd. on page 5)

Printing date 20.05.2021 Version number 48 Revision: 20.05.2021

Trade name DEICHMANN Universalspray 300 ml GB

	(Contd. of page
· Change in condition	
Melting point/freezing point:	Not determined
Initial boiling point and boiling range.	
	Not applicable, as aerosol
Flash point:	-97 °C
	Not applicable, as aerosol
· Inflammability (solid, gaseous)	Not applicable.
Ignition temperature:	200 °C
Decomposition temperature:	Not determined.
Self-inflammability:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive ai
• •	steam mixtures is possible.
Critical values for explosion:	
Lower:	1.0 Vol %
Upper:	8.5 Vol %
Steam pressure at 20 °C:	2100 hPa
Density at 20 °C	0.63768 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
dynamic:	Not determined.
kinematic:	Not determined.
Solvent content:	
Organic solvents:	70.2 %
Solids content:	0.4 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Possible in traces.

Hydrogen chloride.

Hydrogen fluoride

Printing date 20.05.2021 Version number 48 Revision: 20.05.2021

Trade name DEICHMANN Universalspray 300 ml GB

(Contd. of page 5)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity LC50 inhal. >20 g/m3/4h/rat

· LD/LC50 values that are relevant for classification:				
CAS: 64742-49-0 Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane				
Oral	LD50	>5,000 mg/kg (rat) (Acute Oral Toxicity)		
	DNEL consumer	699 mg/kg BW/d (unknown)		
Dermal	LD50	>2,000 mg/kg (rabbit) (Acute Dermal Toxicity)		
	DNEL Worker	733 mg/kg BW/d (unknown)		
	DNEL consumer	699 mg/kg BW/d (unknown)		
Inhalative	LC50/4 h	>20 mg/l (rat) (Acute Inhalation Toxicity)		
	DNEL worker	2,035 mg/kg BW/d (unknown)		
	DNEL consumer	608 mg/m³/24h (unknown)		

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation No irritant effect known.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

· 12.1 Toxicity

Aquatic toxicity: CAS: 64742-49-0 Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
biodegradability	81 %	
IC50/72h	30 mg/l (algae)	
EC50/48 h	30 mg/l (algae) 3 mg/l (daphnia)	
	30 mg/l (algae) (Growth Inhibition Test)	
-	3 mg/l (daphnia) (Daphnientoxizität)	
Acute toxicity fish	11.4 mg/l (fish) (Acute Toxicity Test)	

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class 2 (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

(Contd. on page 7)

Printing date 20.05.2021 Version number 48 Revision: 20.05.2021

Trade name DEICHMANN Universalspray 300 ml GB

(Contd. of page 6)

Danger to drinking water if even small quantities leak into soil.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- \cdot 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN1950
· · · · · · · · · · · · · · · · · · ·	UN1930
14.2 UN proper shipping name ADR	1050 A EDOCOL C. ENVIDONMENTALLY HAZADDOUG
ADK IMDG	1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS AEROSOLS (Hydrocarbons, C6-C7, n-alkanes, isoalkan
IMD 0	cyclics, <5% n-hexane), MARINE POLLUTANT
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
Not applicable.	
Class	2 5F Gases.
Label	2.1
IMDG	
¥2	
Class	2.1
Label	2.1
IATA	
Class	2.1
Label	2.1
14.4 Packing group	
ADR, IMDG, IATA	Void

GB

Printing date 20.05.2021 Version number 48 Revision: 20.05.2021

Trade name DEICHMANN Universalspray 300 ml GB

	(Contd. of page
· 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR):	Product contains environmentally hazardous substances Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user · Kemler Number:	Warning: Gases.
· EMS Number: · Stowage Code	F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre Category A. For AEROSOLS with a capacity above 1 litre
· Segregation Code	Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre Segregation as for class 9. Stow "separated from" class except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Annex Marpol and the IBC Code	x II of Not applicable.
· Transport/Additional information:	Not dangerous according to the above specifications.
· ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category	1L Code: E0 Not permitted as Excepted Quantity 2
· Tunnel restriction code · Remarks:	D Not applicable.
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ) · Remarks:	1L Code: E0 Not permitted as Excepted Quantity Not applicable.
· UN ''Model Regulation'':	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALL HAZARDOUS

SECTION 15: Regulatory information

None of the ingredients is listed.

- \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations
- · Technical instructions (air):

Class	Share in %
II	0.1
III	99.5

(Contd. on page 9)

Printing date 20.05.2021 Version number 48 Revision: 20.05.2021

Trade name DEICHMANN Universalspray 300 ml GB

(Contd. of page 8)

- · Water hazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

Complete H-phrases of the ingredients, if mentioned in chapter 3 "information on ingredients":

H224 Extremely flammable liquid and vapour.

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Department issuing data specification sheet: Product Safety Department

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Aerosol 1: Aerosols - Category 1

Flam. Liq. 1: Flammable liquids - Category 1

Flam. Liq. 2: Flammable liquids - Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

* * Data compared to the previous version altered.