

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 29.03.2022

Version number 49

Revision: 20.05.2021

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name **DEICHMANN Hybrid NL GB 300 ml**

Article number: 10131189000

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture impregnation spray for leather

#### 1.3 Details of the supplier of the safety data sheet

##### Manufacturer/Supplier:

Salzenbrodt GmbH & Co KG  
Internationale Schuh- und Lederpflege  
Hermsdorfer Straße 70  
D-13437 Berlin

Tel.: +49 30 41404-512

##### Informing department:

Product Safety Department, direct call +49 30 41404545; Mobil +49 162 1096464

e-mail: productsafety@collonil.de

##### 1.4 Emergency telephone number:

In case of medical emergency: Poison advisory center Berlin Tel. +49(0)30/30686700

Transport of dangerous goods:

Fire Brigade Bayer AG Tel. +49(0)30/4681-4208

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



flame

Aerosol 1                      H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



environment

Aquatic Chronic 2 H411                      Toxic to aquatic life with long lasting effects.



Skin Irrit. 2                      H315                      Causes skin irritation.

STOT SE 3                      H336                      May cause drowsiness or dizziness.

Asp. Tox. 1                      H304                      May be fatal if swallowed and enters airways.

#### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms GHS02, GHS07, GHS09

Signal word Danger

Hazard-determining components of labelling:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315                      Causes skin irritation.

H336                      May cause drowsiness or dizziness.

H411                      Toxic to aquatic life with long lasting effects.

Precautionary statements

P101                      If medical advice is needed, have product container or label at hand.

(Contd. on page 2)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 29.03.2022

Version number 49

Revision: 20.05.2021

Trade name **DEICHMANN Hybrid NL GB 300 ml**

(Contd. of page 1)

- P102 Keep out of reach of children.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Do not pierce or burn, even after use.  
 P261 Avoid breathing vapours/spray.  
 P271 Use only outdoors or in a well-ventilated area.  
 P312 Call a POISON CENTER/doctor if you feel unwell.  
 P332+P313 If skin irritation occurs: Get medical advice/attention.  
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
 P501 Dispose of contents/container in accordance with local regulations.

### 2.3 Other hazards

The product evidently does not contain any organically bonded halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.

### Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

### 3.2 Chemical characterisation: Mixtures

• **Description:** waterproofing agents in hydrocarbon solvents, filled with propellant

#### Dangerous components:

CAS: 64742-49-0 EC number: 921-024-6	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	50-100%
CAS: 106-97-8 EINECS: 203-448-7	butane, pure Flam. Gas 1, H220; Press. Gas (Comp.), H280	10-<25%
CAS: 74-98-6 EINECS: 200-827-9	propane liquefied Flam. Gas 1, H220; Press. Gas (Comp.), H280	2.5-<10%
CAS: 141-78-6 EINECS: 205-500-4	ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	< 2.5%

• **Additional information** For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

• **After inhalation** In case of unconsciousness bring patient into stable side position for transport.

• **After skin contact** Instantly wash with water and soap and rinse thoroughly.

• **After eye contact** Rinse opened eye for several minutes under running water.

• **After swallowing** In case of persistent symptoms consult doctor.

### 4.2 Most important symptoms and effects, both acute and delayed

Daze

Breathing difficulty

Dizziness

### 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

• **Suitable extinguishing agents** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.

• **For safety reasons unsuitable extinguishing agents**

Water.

Water with a full water jet.

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 29.03.2022

Version number 49

Revision: 20.05.2021

Trade name **DEICHMANN Hybrid NL GB 300 ml**

(Contd. of page 2)

- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.  
see item 7.
- **6.2 Environmental precautions:**  
Do not allow product to reach sewage system or water bodies.  
Inform respective authorities in case product reaches water or sewage system.
- **6.3 Methods and material for containment and cleaning up:**  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling  
See Section 8 for information on personal protection equipment.  
See Section 13 for information on disposal.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Keep containers tightly sealed.  
Store in cool, dry place in tightly closed containers.  
Keep away from heat and direct sunlight.  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle container with care.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.  
Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Buildup of explosive mixtures possible without sufficient ventilation. Keep out of reach of children.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:**  
Store in cool location.  
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep container tightly sealed.  
Store in cool, dry conditions in well sealed containers.  
Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 4)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 29.03.2022

Version number 49

Revision: 20.05.2021

Trade name **DEICHMANN Hybrid NL GB 300 ml**

(Contd. of page 3)

· **Components with critical values that require monitoring at the workplace:**

**CAS: 106-97-8 butane, pure (10-25%)**

WEL Short-term value: 1810 mg/m<sup>3</sup>, 750 ppm  
Long-term value: 1450 mg/m<sup>3</sup>, 600 ppm  
Carc (if more than 0.1% of buta-1.3-diene)

**CAS: 141-78-6 ethyl acetate (<2.5%)**

WEL Short-term value: 1468 mg/m<sup>3</sup>, 400 ppm  
Long-term value: 734 mg/m<sup>3</sup>, 200 ppm

· **Additional information:** The lists that were valid during the compilation were used as basis.

· **8.2 Exposure controls** Not applicable

· **Personal protective equipment**

· **General protective and hygienic measures**

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

Only during spraying without adequate removal by suction.

· **Protection of hands:**

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Nitrile rubber, NBR

Fluorocarbon rubber (Viton)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Fluorocarbon rubber (Viton)

· **Eye protection:** Tightly sealed safety glasses.

**SECTION 9: Physical and chemical properties**

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Aerosol

Colour: Colourless

· **Smell:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

(Contd. on page 5)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 29.03.2022

Version number 49

Revision: 20.05.2021

Trade name **DEICHMANN Hybrid NL GB 300 ml**

(Contd. of page 4)

· <b>Change in condition</b>	
<b>Melting point/freezing point:</b>	Not determined
<b>Initial boiling point and boiling range:</b>	-48 °C Not applicable, as aerosol
· <b>Flash point:</b>	-97 °C Not applicable, as aerosol
· <b>Inflammability (solid, gaseous)</b>	Not applicable.
· <b>Ignition temperature:</b>	200 °C
· <b>Decomposition temperature:</b>	Not determined.
· <b>Self-inflammability:</b>	Product is not selfigniting.
· <b>Explosive properties:</b>	Product is not explosive. However, formation of explosive air/steam mixtures is possible.
· <b>Critical values for explosion:</b>	
<b>Lower:</b>	1.0 Vol %
<b>Upper:</b>	8.5 Vol %
· <b>Steam pressure at 20 °C:</b>	2100 hPa
· <b>Density at 20 °C</b>	0.63768 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not applicable.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix
· <b>Partition coefficient: n-octanol/water:</b>	Not determined.
· <b>Viscosity:</b>	
<b>dynamic:</b>	Not determined.
<b>kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	70.2 %
<b>Solids content:</b>	0.4 %
· <b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**  
Possible in traces.  
Hydrogen chloride.  
Hydrogen fluoride

GB

(Contd. on page 6)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 29.03.2022

Version number 49

Revision: 20.05.2021

Trade name **DEICHMANN Hybrid NL GB 300 ml**

(Contd. of page 5)

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity LC50 inhal.** >20 g/m<sup>3</sup>/4h/rat

- **LD/LC50 values that are relevant for classification:**

**CAS: 64742-49-0 Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane**

Oral	LD50	>5,000 mg/kg (rat) (Acute Oral Toxicity)
	DNEL consumer	699 mg/kg BW/d (unknown)
Dermal	LD50	>2,000 mg/kg (rabbit) (Acute Dermal Toxicity)
	DNEL Worker	733 mg/kg BW/d (unknown)
	DNEL consumer	699 mg/kg BW/d (unknown)
Inhalative	LC50/4 h	>20 mg/l (rat) (Acute Inhalation Toxicity)
	DNEL worker	2,035 mg/kg BW/d (unknown)
	DNEL consumer	608 mg/m <sup>3</sup> /24h (unknown)

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation** No irritant effect known.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard**  
May be fatal if swallowed and enters airways.

### SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

**CAS: 64742-49-0 Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane**

biodegradability	81 %
IC50/72h	30 mg/l (algae)
EC50/48 h	3 mg/l (daphnia)
Toxicity to aquatic invertebrates	30 mg/l (algae) (Growth Inhibition Test) 3 mg/l (daphnia) (Daphnientoxizität)
Acute toxicity fish	11.4 mg/l (fish) (Acute Toxicity Test)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

- **Ecotoxicological effects:**

- **Remark:** Toxic for fish

- **Additional ecological information:**

- **General notes:**

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class 2 (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 29.03.2022

Version number 49

Revision: 20.05.2021

Trade name **DEICHMANN Hybrid NL GB 300 ml**




(Contd. of page 6)

- *Danger to drinking water if even small quantities leak into soil.*
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

- **14.1 UN-Number**  
· **ADR, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**  
· **ADR** 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS  
· **IMDG** AEROSOLS (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane), MARINE POLLUTANT  
· **IATA** AEROSOLS, flammable
- **14.3 Transport hazard class(es)**
- **ADR**  
  
 Not applicable.  
 · **Class** 2.5F Gases.  
 · **Label** 2.1
- **IMDG**  
  
 · **Class** 2.1 Gases.  
 · **Label** 2.1
- **IATA**  
  
 · **Class** 2.1 Gases.  
 · **Label** 2.1
- **14.4 Packing group**  
· **ADR, IMDG, IATA** Void

(Contd. on page 8)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 29.03.2022

Version number 49

Revision: 20.05.2021

Trade name **DEICHMANN Hybrid NL GB 300 ml**

(Contd. of page 7)

· <b>14.5 Environmental hazards:</b>	Product contains environmentally hazardous substances: Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane
· <b>Marine pollutant:</b>	Symbol (fish and tree)
· <b>Special marking (ADR):</b>	Symbol (fish and tree)
· <b>14.6 Special precautions for user</b>	Warning: Gases.
· <b>Kemler Number:</b>	-
· <b>EMS Number:</b>	F-D,S-U
· <b>Stowage Code</b>	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· <b>Segregation Code</b>	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	Not dangerous according to the above specifications.
· <b>ADR</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>Transport category</b>	2
· <b>Tunnel restriction code</b>	D
· <b>Remarks:</b>	Not applicable.
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>Remarks:</b>	Not applicable.
· <b>UN "Model Regulation":</b>	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

### SECTION 15: Regulatory information

None of the ingredients is listed.

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· National regulations

· Technical instructions (air):

Class	Share in %
II	0.1
III	99.5

(Contd. on page 9)

GB



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 29.03.2022

Version number 49

Revision: 20.05.2021

Trade name **DEICHMANN Hybrid NL GB 300 ml**

(Contd. of page 8)

- **Water hazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

*These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

- **Relevant phrases**

*Complete H-phrases of the ingredients, if mentioned in chapter 3 "information on ingredients":*

- H220 Extremely flammable gas.*
- H225 Highly flammable liquid and vapour.*
- H280 Contains gas under pressure; may explode if heated.*
- H304 May be fatal if swallowed and enters airways.*
- H315 Causes skin irritation.*
- H319 Causes serious eye irritation.*
- H336 May cause drowsiness or dizziness.*
- H411 Toxic to aquatic life with long lasting effects.*

- **Department issuing data specification sheet:** Product Safety Department

- **Abbreviations and acronyms:**

*ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*IATA: International Air Transport Association*

*GHS: Globally Harmonised System of Classification and Labelling of Chemicals*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*PBT: Persistent, Bioaccumulative and Toxic*

*vPvB: very Persistent and very Bioaccumulative*

*Flam. Gas 1: Flammable gases – Category 1*

*Aerosol 1: Aerosols – Category 1*

*Press. Gas (Comp.): Gases under pressure – Compressed gas*

*Flam. Liq. 2: Flammable liquids – Category 2*

*Skin Irrit. 2: Skin corrosion/irritation – Category 2*

*Eye Irrit. 2: Serious eye damage/eye irritation – Category 2*

*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*

*Asp. Tox. 1: Aspiration hazard – Category 1*

*Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2*

- **\* Data compared to the previous version altered.**

GB