Printing date 29.03.2022

Version number 49

Revision: 20.05.2021

inting date 29	.03.2022	Version number 49	<i>Revision: 20.05.2021</i>
SECTION	V 1: Identifica	tion of the substance/mixture and of the	company/undertaking
· 1.1 Product	identifier		
	•	Universalspray 300 ml NL	
• <b>Article num</b> • <b>1.2 Relevan</b> No further r	<b>ber:</b> 182311890 <b>t identified uses</b> elevant informat	00 of the substance or mixture and uses advised aga	inst
• <b>Manufactur</b> Salzenbrodt	<b>er/Supplier:</b> GmbH & Co K( tle Schuh- und L r Straße 70		Tel.: +49 30 41404-512
e-mail: prod • <b>1.4 Emerge</b> In case of m Transport oj	ety Departement luctsafety@collo <b>ncy telephone n</b> edical emergenc f dangerous good	<b>umber:</b> y: Poison advisory center Berlin Tel.+49(0)30/30	
· 2.1 Classific		stance or mixture Regulation (EC) No 1272/2008	
JAKE AL	ame		
	anne		
Aerosol 1	Н222-Н2	229 Extremely flammable aerosol. Pressurised con	tainer: May burst if heated.
SV.			
<u> Т/2</u> ег	wironment		
Aquatic Chr	omia ) U/11	Toxic to gaugic life with long lasting effects	
	onic 2 H411	Toxic to aquatic life with long lasting effects.	
Skin Irrit. 2	H315	Causes skin irritation.	
STOT SE 3	H315 H336	May cause drowsiness or dizziness.	
Asp. Tox. 1		May be fatal if swallowed and enters airways.	
• 2.2 Label el • Labelling ad The product	ements ccording to Regi is classified and ograms GHS02,	Ilation (EC) No 1272/2008 labelled according to the GB CLP regulation. GHS07, GHS09	
0	-	nents of labelling:	
Hydrocarbo	ns, C6-C7, n-alk	anes, isoalkanes, cyclics, <5% n-hexane	
• Hazard state H222-H229		nable aerosol. Pressurised container: May burst if	`heated.
H315	Causes skin irri	tation.	
		vsiness or dizziness.	
H411 • <b>Precaution</b>	Toxic to aquatic a <b>ry statements</b>	life with long lasting effects.	
P101		e is needed, have product container or label at ha	nd.
	-	•	(Contd. on page 2)

(Contd. on page 2)

Printing date 29.03.2022

Version number 49

Revision: 20.05.2021

(Contd. of page 1)

### Trade name DEICHMANN Universalspray 300 ml NL

P102 Keep out of reach of children.

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- *P211* Do not spray on an open flame or other ignition source.
- *P251* Do not pierce or burn, even after use.
- P261 Avoid breathing vapours/spray.
- *P271* Use only outdoors or in a well-ventilated area.
- P312 Call a POISON CENTER/doctor if you feel unwell.
- *P332+P313 If skin irritation occurs: Get medical advice/attention.*
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- *P501* Dispose of contents/container in accordance with local regulations.

### · 2.3 Other hazards

The product evidently does not contain any organically bonded halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

## **SECTION 3: Composition/information on ingredients**

· 3.2 Chemical characterisation: Mixtures

· Description: waterproofing agents in hydrocarbon solvents, filled with propellant

### · Dangerous components:

Dungerous components.		
	<i>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</i>	50-100%
EC number: 921-024-6	♦ Flam. Liq. 2, H225; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ Skin Irrit. 2, H315; STOT SE 3, H336	
CAS: 106-97-8	butane, pure	10-<25%
EINECS: 203-448-7	🚸 Flam. Gas 1, H220; Press. Gas (Comp.), H280	
CAS: 74-98-6	propane liquefied	2.5-<10%
EINECS: 200-827-9	🚸 Flam. Gas 1, H220; Press. Gas (Comp.), H280	
CAS: 141-78-6	ethyl acetate	< 2.5%
EINECS: 205-500-4	🚸 Flam. Liq. 2, H225; 🚸 Eye Irrit. 2, H319; STOT SE 3, H336	
· Additional information	For the wording of the listed hazard phrases refer to section 16	

 $\cdot$  Additional information For the wording of the listed hazard phrases refer to section 16.

## **SECTION 4: First aid measures**

• 4.1 Description of first aid measures

- After inhalation In case of unconsciousness bring patient into stable side position for transport.
- After skin contact Instantly wash with water and soap and rinse thoroughly.
- After eye contact Rinse opened eye for several minutes under running water.
- · After swallowing In case of persistent symptoms consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
- Daze

Breathing difficulty

Dizziness

• **4.3 Indication of any immediate medical attention and special treatment needed** *No further relevant information available.* 

## **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- Suitable extinguishing agents CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents
- Water.

Water with a full water jet.

(Contd. on page 3)

GB

Printing date 29.03.2022

Version number 49

Revision: 20.05.2021

(Contd. of page 2)

#### Trade name DEICHMANN Universalspray 300 ml NL

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- *Protective equipment:* No special measures required.

## **SECTION 6:** Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. see item 7.
- 6.2 Environmental precautions: Do not allow product to reach sewage system or water bodies.
- Inform respective authorities in case product reaches water or sewage system.
- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
- 6.4 Reference to other sections See Section 7 for information on safe handling See Section 8 for information on personal protection equipment. See Section 13 for information on disposal.

## **SECTION 7: Handling and storage**

7.1 Precautions for safe handling Keep containers tightly sealed.
Store in cool, dry place in tightly closed containers.
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
Open and handle container with care.

 Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric

lights. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Buildup of explosive mixtures possible without sufficient ventilation. Keep out of reach of children.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage
- *Requirements to be met by storerooms and containers:* Store in cool location.
- Observe official regulations on storing packagings with pressurised containers.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep container tightly sealed.

Store in cool, dry conditions in well sealed containers.

Protect from heat and direct sunlight.

• 7.3 Specific end use(s) No further relevant information available.

## **SECTION 8: Exposure controls/personal protection**

· 8.1 Control parameters

• Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 4)

GB

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.03.2022

Version number 49

Revision: 20.05.2021

# Trade name DEICHMANN Universalspray 300 ml NL

CAS: 106 WEL Sho Lor Car	with critical values that require monitoring at the workplace: -8 butane, pure (10-25%) erm value: 1810 mg/m <sup>3</sup> , 750 ppm
WEL Sho Lor Car	erm value: 1810 mg/m <sup>3</sup> , 750 ppm
Lor Car	
Car	
	$erm value: 1450 mg/m^3, 600 ppm$
('AS' 14)	f more than 0.1% of buta-1.3-diene)
	-6 ethyl acetate (<2.5%)
	erm value: 1468 mg/m³, 400 ppm erm value: 734 mg/m³, 200 ppm
	formation: The lists that were valid during the compilation were used as basis.
	controls Not applicable
	tective equipment ective and hygienic measures
	om foodstuffs, beverages and food.
	ove any soiled and impregnated garments.
	luring breaks and at the end of the work.
	gases / fumes / aerosols.
	t with the skin.
	t with the eyes and skin.
· Breathing	
	ief exposure or low pollution use breathing filter apparatus. In case of intensive or lon
	breathing apparatus that is independent of circulating air.
	praying without adequate removal by suction.
· Protection	
Protective	
	terial has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to m	g tests no recommendation to the glove material can be given for the product/ the preparati
the chemi	
	the glove material on consideration of the penetration times, rates of diffusion and
degradati	
• Material	
Nitrile ru	
	n rubber (Viton)
and varie	of the suitable gloves does not only depend on the material, but also on further marks of qua om manufacturer to manufacturer. As the product is a preparation of several substances, the glove material can not be calculated in advance and has therefore to be checked prior to
	ime of glove material
	eak trough time has to be found out by the manufacturer of the protective gloves and has to
observed.	
· For the p	nanent contact of a maximum of 15 minutes gloves made of the following materials
suitable:	
	n rubber (Viton)
· Eye prote	n: Tightly sealed safety glasses.
SECTL	9: Physical and chemical properties
	2. Thysical and chemical properties
· 9.1 Inform	on on basic physical and chemical properties
· General I	
· Appearan	
Form:	Aerosol
	Colourless
Colour:	Characteristic
Colour: · Smell:	
	old: Not determined.
Smell:	old: Not determined. Not determined.

Printing date 29.03.2022

Version number 49

Revision: 20.05.2021

Trade name DEICHMANN Universalspray 300 ml NL

	(Contd. of page
Change in condition Melting point/freezing point: Initial boiling point and boiling range.	Not determined : -48 °C
	Not applicable, as aerosol
Flash point:	-97 °C
	Not applicable, as aerosol
Inflammability (solid, gaseous)	Not applicable.
Ignition temperature:	200 °C
Decomposition temperature:	Not determined.
Self-inflammability:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air steam mixtures is possible.
Critical values for explosion:	
Lower:	1.0 Vol %
Upper:	8.5 Vol %
Steam pressure at 20 °C:	2100 hPa
Density at 20 °C	0.63768 g/cm <sup>3</sup>
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
dynamic:	Not determined.
kinematic:	Not determined.
Solvent content:	
Organic solvents:	70.2 %
Solids content:	0.4 %
9.2 Other information	No further relevant information available.

# **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:
- Possible in traces.
- Hydrogen chloride.
- Hydrogen fluoride

(Contd. on page 6)

Printing date 29.03.2022

Version number 49

Revision: 20.05.2021

## Trade name DEICHMANN Universalspray 300 ml NL

(Contd. of page 5)

950 NEL consumer 950 NEL Worker NEL consumer 950/4 h NEL worker	ons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane >5,000 mg/kg (rat) (Acute Oral Toxicity) 699 mg/kg BW/d (unknown) >2,000 mg/kg (rabbit) (Acute Dermal Toxicity) 733 mg/kg BW/d (unknown) 699 mg/kg BW/d (unknown) >20 mg/l (rat) (Acute Inhalation Toxicity) 2,035 mg/kg BW/d (unknown) 608 mg/m <sup>3</sup> /24h (unknown)
VEL consumer 150 VEL Worker VEL consumer 150/4 h VEL worker VEL consumer Int effect: n/irritation ritation. umage/irritation	699 mg/kg BW/d (unknown) >2,000 mg/kg (rabbit) (Acute Dermal Toxicity) 733 mg/kg BW/d (unknown) 699 mg/kg BW/d (unknown) >20 mg/l (rat) (Acute Inhalation Toxicity) 2,035 mg/kg BW/d (unknown)
950 NEL Worker NEL consumer S50/4 h NEL worker NEL consumer <b>nt effect:</b> <b>n/irritation</b> ritation. <b>umage/irritatio</b>	>2,000 mg/kg (rabbit) (Acute Dermal Toxicity) 733 mg/kg BW/d (unknown) 699 mg/kg BW/d (unknown) >20 mg/l (rat) (Acute Inhalation Toxicity) 2,035 mg/kg BW/d (unknown)
VEL Worker VEL consumer 250/4 h VEL worker VEL consumer VEL consumer Int effect: n/irritation ritation. umage/irritation	733 mg/kg BW/d (unknown) 699 mg/kg BW/d (unknown) >20 mg/l (rat) (Acute Inhalation Toxicity) 2,035 mg/kg BW/d (unknown)
VEL consumer 50/4 h VEL worker VEL consumer <b>nt effect:</b> <b>n/irritation</b> ritation. <b>umage/irritatio</b>	699 mg/kg BW/d (unknown) >20 mg/l (rat) (Acute Inhalation Toxicity) 2,035 mg/kg BW/d (unknown)
50/4 h NEL worker NEL consumer <b>nt effect:</b> <b>n/irritation</b> ritation. <b>umage/irritation</b>	>20 mg/l (rat) (Acute Inhalation Toxicity) 2,035 mg/kg BW/d (unknown)
VEL consumer <b>nt effect:</b> <b>n/irritation</b> ritation. <b>1mage/irritation</b>	
nt effect: n/irritation ritation. 1mage/irritatio1	608 mg/m <sup>3</sup> /24h (unknown)
nt effect: n/irritation ritation. 1mage/irritatio1	
ity Based on ave toxicity Based of exposure owsiness or dizz ed exposure Bas zard	ailable data, the classification criteria are not met. on available data, the classification criteria are not met. riness. sed on available data, the classification criteria are not met.
12: Ecologic	al information
	oxicity Based ( xxposure wwsiness or dizz d exposure Bas gard <sup>c</sup> swallowed and

Acute toxicity fish

EC50/48 h

· 12.2 Persistence and degradability No further relevant information available.

Toxicity to aquatic invertebrates 30 mg/l (algae) (Growth Inhibition Test)

3 mg/l (daphnia)

3 mg/l (daphnia) (Daphnientoxizität)

11.4 mg/l (fish) (Acute Toxicity Test)

· 12.3 Bioaccumulative potential No further relevant information available.

· 12.4 Mobility in soil No further relevant information available.

· Ecotoxical effects:

• **Remark:** Toxic for fish

• Additional ecological information:

· General notes:

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class 2 (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

(Contd. on page 7)

GB

Printing date 29.03.2022

Version number 49

Revision: 20.05.2021

(Contd. of page 6)

### Trade name DEICHMANN Universalspray 300 ml NL

- Danger to drinking water if even small quantities leak into soil.
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

# **SECTION 13: Disposal considerations**

• 13.1 Waste treatment methods

· Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

· 14.1 UN-Number · ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name · ADR · IMDG	1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS AEROSOLS (Hydrocarbons, C6-C7, n-alkanes, isoalkan cyclics, <5% n-hexane), MARINE POLLUTANT
·IATA	AEROSOLS, flammable
· 14.3 Transport hazard class(es)	
ADR	
Not applicable.	
· Class	2 5F Gases.
· Label · IMDG	2.1
· Class	2.1 Gases.
· Label	2.1
· IATA	
· Class	2.1 Gases.
·Label	2.1
· 14.4 Packing group · ADR, IMDG, IATA	Void

Printing date 29.03.2022

Version number 49

Revision: 20.05.2021

### Trade name DEICHMANN Universalspray 300 ml NL

	(Contd. of page
14.5 Environmental hazards: Marine pollutant:	Product contains environmentally hazardous substances Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <59 n-hexane Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user Kemler Number: EMS Number: Stowage Code	Warning: Gases. - F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre Category A. For AEROSOLS with a capacity above 1 litre Category B. For WASTE AEROSOLS: Category C, Clea
Segregation Code	of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre. Segregation as for class 9. Stow "separated from" class except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
14.7 Transport in bulk according to Anne	x II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	Not dangerous according to the above specifications.
ADR	
Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
Transport category Tunnel restriction code Remarks:	2 D Not applicable.
IMDG	
Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
Remarks:	Not applicable.
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALL HAZARDOUS

# **SECTION 15: Regulatory information**

None of the ingredients is listed.

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· National regulations

• Technical instructions (air):

 Class
 Share in %

 II
 0.1

 III
 99.5

(Contd. on page 9)

Printing date 29.03.2022

Version number 49

Revision: 20.05.2021

### Trade name DEICHMANN Universalspray 300 ml NL

(Contd. of page 8)

• Water hazard class: Water hazard class 2 (Self-assessment): hazardous for water.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **SECTION 16: Other information**

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

Complete H-phrases of the ingredients, if mentioned in chapter 3 "information on ingredients": H220 Extremely flammable gas. H225 Highly flammable liquid and vapour. H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. · Department issuing data specification sheet: Product Safety Department • Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases - Category 1 Aerosol 1: Aerosols – Category 1 Press. Gas (Comp.): Gases under pressure - Compressed gas Flam. Liq. 2: Flammable liquids - Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 • \* Data compared to the previous version altered.